PATENT ABSTRACTS OF JAPAN

(11)Publication number:

01-256101

(43) Date of publication of application: 12.10.1989

(51)Int.Cl.

H01C 7/00

(21)Application number : 63-084938

(71)Applicant: SEIKO INSTR INC

(22)Date of filing:

06.04.1988

(72)Inventor: SANHONGI NORIMITSU

(54) THIN FILM TYPE THERMAL HEAD

(57)Abstract:

PURPOSE: To realize the high speed operation of a thermal head, and improve the high temperature stability, by making the temperature coefficient of resistance of Ta-SiO2 as a thin film heater resistor approximate to zero.



CONSTITUTION: The temperature coefficient of resistance TCR of a thin film heating resistor 2 composed of tantalum-silicon oxide (Ta-SiO2) is made 0 to -500ppm in the resistivity range of 1-100m Ω .cm. As a result, the TCR can be almost equal to zero, by performing Ta-SiO2 sputtering, wherein a target whose SiO2 mol ratio in the target composition ratio is in a



range of 30-70%, and argon gas pressure is kept about 10-2Torr. Thereby, the high speed operation of a thermal

head is realized, and the improvement of high temperature stability and durability can be easily attained.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

Kind of final disposal of application other than



the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

PAT-NO:

JP401256101A

DOCUMENT-IDENTIFIER: JP 01256101 A

TITLE:

THIN FILM TYPE THERMAL HEAD

PUBN-DATE:

October 12, 1989

INVENTOR-INFORMATION:

NAME

SANHONGI, NORIMITSU

ASSIGNEE-INFORMATION:

NAME

COUNTRY

SEIKO INSTR INC

N/A

APPL-NO:

JP63084938

APPL-DATE:

April 6, 1988

INT-CL (IPC): H01C007/00, B41J003/20

US-CL-CURRENT: 338/60

ABSTRACT:

PURPOSE: To realize the high speed operation of a thermal head, and improve the high temperature stability, by making the temperature coefficient of resistance of Ta-SiO<SB>2</SB> as a thin film heater resistor approximate to zero.

CONSTITUTION: The temperature coefficient of resistance TCR of a thin film heating resistor 2 composed of tantalum-silicon oxide (Ta-SiO < SB > 2 < /SB >) is made 0 to -500ppm in the resistivity range of 1-100mΩ.cm. As a result, the TCR can be almost equal to zero, by performing

Ta-SiO<SB>2</SB> sputtering, wherein a target whose SiO<SB>2</SB> mol ratio in the target composition ratio is in a range of 30-70%, and argon gas pressure is kept about 10<SP>-2</SP>Torr. Thereby, the high speed operation of a thermal head is realized, and the improvement of high temperature stability and durability can be easily attained.

COPYRIGHT: (C) 1989, JPO&Japio